

Platamid® H 2528 Powder

PA*

ARKEMA

Product Texts

Platamid® H 2528 Powder

Copolyamide Hot Melt Adhesive / Textile Applications

Platamid® H 2528 Powder is a medium melt viscosity copolyamide adhesive powder for the production of fusible interlinings. **Platamid® H 2528 Powder** offers excellent laundry resistance up to 60°C and an excellent steam resistance at moderate fusing conditions.

AVAILABLE GRADES

This grade is available in different grain sizes:

- Platamid® H 2528 PA80 (0-80 µm paste dot)
- Platamid® H 2528 PTA 120 (0-120 µm power dot)
- Platamid® H 2528 PTA 170/20 (0-170 µm power dot)
- Platamid® H 2528 PTA 170 (80-170 µm double dot)

PACKAGING

Platamid® H 2528 PTA 170, Platamid® H 2528 PA80, Platamid® H 2528 PTA 120 and Platamid® H 2528 PTA 170/20 are delivered in 20 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melt volume-flow rate, MVR	44 / *	cm ³ /10min	ISO 1133
Temperature	160 / *	°C	-
Load	2.16 / *	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melting temperature, 10°C/min	128 / *	°C	ISO 11357-1/-3

[C]: CAMPUS

Characteristics

Delivery form

Powder

Features

Copolymer

Regional Availability

North America, Europe, Asia Pacific, South and Central America, Near East/Africa