

Platamid® M 1422 Pellets

PA*

ARKEMA

Product Texts

Platamid® M 1422 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® M 1422 Pellets is a standard thermoplastic copolyamide hot melt adhesive available in pellet form and is used in solvent based processes.

Platamid® M 1422 Pellets is a semi-crystallized copolyamide product which has been developed for use in the wire coating industry.

AVAILABLE GRADES

This product is available:

- undried (M 1422 F)
- undried (M 1422/1 F)

PACKAGING

- Platamid® M 1422 F and M 1422/1 F are delivered in 25 kg sealed bags.

These grades are ready to be processed.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melt volume-flow rate, MVR	30 / *	cm ³ /10min	ISO 1133
Temperature	230 / *	°C	-
Load	2.16 / *	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melting temperature, 10°C/min	120 / *	°C	ISO 11357-1/-3

[C]: CAMPUS

Characteristics

Processing

Film Extrusion, Coating

Features

Copolymer

Delivery form

Pellets

Regional Availability

North America, Europe, Asia Pacific, South and Central America, Near East/Africa