

**Product Texts**

**Platamid® M 2395 Pellets**

Copolyamide Hot Melt Adhesive /Extrusion Applications

**Platamid® M 2395 Pellets** are a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This medium melt viscosity grade is particularly suitable for manufacturing of webs, nets, mono-and multi-filaments, and films by extrusion.

**Platamid® M 2395 Pellets** offer very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc), strong adhesion onto rigid and plastcized PVC as well as ABS, epoxy resin, PU etc. Dense layers of Platamid® M 2395 are know to have barrier properties against PVC plasticizer migration.

**AVAILABLE GRADES**

This grade is available:

- dried (M 2395 T)

**PACKAGING**

Platamid® M 2395 T is delivered in 100 kg sealed rigid container (GRVC).

This grade is ready to be processed

**SHELFLIFE**

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

**RENEWABLE CARBON CONTENT : 33% (Internal method)**

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melt volume-flow rate, MVR	8 / *	cm³/10min	ISO 1133
Temperature	160 / *	°C	-
Load	2.16 / *	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melting temperature, 10°C/min	107 / *	°C	ISO 11357-1/-3

[C]: CAMPUS

Other properties	Value	Unit	Test Standard
Biobased content	33	%	-

**Characteristics**

**Processing**

Film Extrusion

**Certifications**

Contains renewable resources

**Delivery form**

Pellets

**Applications**

Monofilament, Multifilament

**Features**

Barrier Properties, Good Adhesion, Copolymer

**Regional Availability**

North America, Europe, Asia Pacific, South and Central America, Near East/Africa