

**8150 White 91**

PVC

Westlake Chemical Corp.

<b>Mechanical properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
<b>ASTM Data</b>			
Tensile Modulus	<b>3578</b>	MPa	ASTM D 638
Tensile Strength	<b>48.1</b>	MPa	ASTM D 638
Flexural Modulus	<b>2654</b>	MPa	ASTM D 790
Flexural Strength	<b>79</b>	MPa	ASTM D 790
Izod Impact notched, 1/8 in	<b>1010</b>	J/m	ASTM D 256
Izod Impact notched, 1/4 in	<b>149</b>	J/m	ASTM D 256

<b>Thermal properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
<b>ASTM Data</b>			
DTUL @ 66 psi	<b>65.8</b>	°C	ASTM D 648
DTUL @ 264 psi	<b>59.9</b>	°C	ASTM D 648

<b>Other properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Density	<b>1460</b>	kg/m <sup>3</sup>	ASTM D 792

**Characteristics****Delivery form**

White

**Regional Availability**

North America