

Product Texts

Platamid® H 38 Pellets

Copolyamide Hot Melt Adhesive

Platamid® H 38 is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This low to medium melt viscosity grade is particularly suitable for manufacturing webs, nets, mono- and multi-filaments and films by extrusion.

Platamid® H 38 offers very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

AVAILABLE GRADES

This grade is available:

- dried with optical brightener (H 38 TA)
- undried with optical brightener (H 38 FA)

PACKAGING

Platamid® H 38 TA is delivered in 25 kg sealed bags.

Platamid® H 38 FA is delivered in 500 kg sealed big bags (GRVS).

These grades are ready to be processed

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melt volume-flow rate, MVR	23 / *	cm ³ /10min	ISO 1133
Temperature	160 / *	°C	-
Load	2.16 / *	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melting temperature, 10°C/min	109 / *	°C	ISO 11357-1/-3

[C]: CAMPUS

Other properties	dry / cond	Unit	Test Standard
^[C] Density	1070 / 1070	kg/m ³	ISO 1183

[C]: CAMPUS

Characteristics

Processing

Other Extrusion

Applications

Monofilament, Multifilament

Delivery form

Pellets

Regional Availability

North America, Europe, Asia Pacific, South and Central America, Near East/Africa

Features

Good Adhesion, Copolymer