

**Product Texts**

**Platamid® H 1937 Pellets**

Copolyamide Hot Melt Adhesive / Extrusion Applications

**Platamid® H 1937** is a thermoplastic copolyamide adhesive available in pellet form for manufacture of hot melt film and webs by extrusion.

**Platamid® H 1937** has good adhesion to all kinds of textile substrates based on native and synthetic fibers.

**AVAILABLE GRADES**

This product is available:

- dried (H 1937 TA)

**PACKAGING**

- Platamid® H 1937 TA is delivered in 25 kg sealed bags.

This grade is ready to be processed.

**SHELF LIFE**

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melt volume-flow rate, MVR	18 / *	cm <sup>3</sup> /10min	ISO 1133
Temperature	160 / *	°C	-
Load	2.16 / *	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melting temperature, 10°C/min	102 / *	°C	ISO 11357-1/-3

[C]: CAMPUS

**Characteristics**

**Processing**

Film Extrusion

**Features**

Good Adhesion, Copolymer

**Delivery form**

Pellets

**Regional Availability**

North America, Europe, Asia Pacific, South and Central America, Near East/Africa