

**Product Texts**

**Platamid® H 2516 Pellets**

Copolyamide Hot Melt Adhesive

**Platamid® H 2516** is a thermoplastic copolyamide hot melt adhesive available in pellet form. This fast re-crystallizing grade has been developed to manufacture hot-melt webs, nets and mono- and multi-filaments.

**Platamid® H 2516** offers a very good adhesion to all kinds of textile substrates based on native and synthetic fibers. Additionally **Platamid® H 2516** provides elastomeric properties and high water vapor transmission rate.

**AVAILABLE GRADES**

This grade is available:

- Undried with optical brightener (H 2516 FA)

**PACKAGING**

Platamid® H 2516 FA is delivered in 500 kg sealed bags (GRVS) and 500 kg sealed rigid container (GRVC). These grades are ready to be processed.

**SHELF LIFE**

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melt volume-flow rate, MVR	<b>85 / *</b>	cm <sup>3</sup> /10min	ISO 1133
Temperature	<b>160 / *</b>	°C	-
Load	<b>2.16 / *</b>	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melting temperature, 10°C/min	<b>108 / *</b>	°C	ISO 11357-1/-3

[C]: CAMPUS

**Characteristics**

**Delivery form**

Pellets

**Applications**

Monofilament, Multifilament

**Features**

Good Adhesion, Copolymer

**Regional Availability**

North America, Europe, Asia Pacific, South and Central America, Near East/Africa