

Product Texts

Platamid® HX 2651 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® HX 2651 Pellets is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This low melt viscosity grade is particularly suitable for manufacturing webs and nets by extrusion.

Platamid® HX 2651 Pellets offers good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.) thanks to its amine functionality groups.

AVAILABLE GRADES

This grade is available:

- Platamid® HX 2651 FA Pellets(undried)

PACKAGING

- Platamid® HX 2651 is delivered in 25 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melt volume-flow rate, MVR	36 / *	cm ³ /10min	ISO 1133
Temperature	130 / *	°C	-
Load	2.16 / *	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melting temperature, 10°C/min	105 / *	°C	ISO 11357-1/-3

[C]: CAMPUS

Characteristics

Processing

Film Extrusion

Features

Good Adhesion, Copolymer

Delivery form

Pellets

Regional Availability

North America, Europe, Asia Pacific, South and Central America, Near East/Africa