

Product Texts

Platamid® HX 2651 Powder

Copolyamide Hot Melt Adhesive / Textile Applications

Platamid® HX 2651 Powder is a very high melt viscosity standard copolyamide adhesive powder for the production of fusible interlinings.

Platamid® HX 2651 Powder offers excellent laundry resistance up to 40°C. This super fluid product permits better penetration to treated fabric.

AVAILABLE GRADES

This powder grade is available in different grain sizes:

- Platamid® HX 2651 PA80 (0-80 µm paste dot)
- Platamid® HX 2651 PTA 170 (80-170 µm double dot)
- Platamid® HX 2651 PRA 170 (80-170 µm double dot)
- Platamid® HX 2651 PTA 60 (80-120 µm powder dot)

PACKAGING

- Platamid® HX 2651 powder is delivered in 20 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melt volume-flow rate, MVR	195 / *	cm ³ /10min	ISO 1133
Temperature	160 / *	°C	-
Load	2.16 / *	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
ISO Data			
^[C] Melting temperature, 10°C/min	115 / *	°C	ISO 11357-1/-3

[C]: CAMPUS

Characteristics

Delivery form

Powder

Features

Copolymer

Regional Availability

North America, Europe, Asia Pacific, South and Central America, Near East/Africa