

**Product Texts**

**Platamid® HX 2671 Pellets**

Copolyamide Hot Melt Adhesive / Extrusion Applications

**Platamid® HX 2671** is a standard thermoplastic co-polyamide hot melt adhesive available in pellet form. This very low melt viscosity, fast re-crystallizing grade is particularly suitable for spraying, manufacturing webs, nets, mono- and multi-filaments, and films by extrusion. **Platamid® HX 2671** offers a very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

**Platamid® HX 2671** has a very good dry-cleaning resistance and washing resistance up to 40°C.

**AVAILABLE GRADES**

This grade is available:

- undried (HX 2671 F)

**PACKAGING**

Platamid® HX 2671 is delivered in 25 kgs sealed bags.

**SHELF LIFE**

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

Processing/Physical Characteristics	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melt volume-flow rate, MVR	<b>148 / *</b>	cm <sup>3</sup> /10min	ISO 1133
Temperature	<b>160 / *</b>	°C	-
Load	<b>2.16 / *</b>	kg	-

[C]: CAMPUS

Thermal properties	dry / cond	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melting temperature, 10°C/min	<b>122 / *</b>	°C	ISO 11357-1/-3

[C]: CAMPUS

**Characteristics**

**Processing**

Film Extrusion, Other Extrusion

**Certifications**

Contains renewable resources

**Delivery form**

Pellets

**Applications**

Monofilament, Multifilament

**Features**

Good Adhesion, Copolymer

**Regional Availability**

North America, Europe, Asia Pacific, South and Central America, Near East/Africa