

**Product Texts**

SABIC® PP 108MF10 is a super high impact copolymer which exhibits an unmatched cold impact resistance, high flow and excellent paint adhesion characteristics. Because of this unique and well balanced property profile our customers commonly use this material for painted car bumpers. SABIC® PP 108MF10 is a designated automotive grade. IMDS ID: 80775790

<b>Mechanical properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
<b>ISO Data</b>			
Tensile Modulus	<b>1000</b>	MPa	ISO 527
Yield stress	<b>19</b>	MPa	ISO 527
Yield strain	<b>8</b>	%	ISO 527
Charpy impact strength, +23°C	<b>N</b>	kJ/m <sup>2</sup>	ISO 179/1eU
Charpy notched impact strength, +23°C	<b>N</b>	kJ/m <sup>2</sup>	ISO 179/1eA
Izod notched impact strength	<b>35</b>	kJ/m <sup>2</sup>	ISO 180/1A
Shore D hardness	<b>52</b>	-	ISO 7619-1

<b>Thermal properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
<b>ISO Data</b>			
Vicat softening temperature, A	<b>130</b>	°C	ISO 306
Vicat softening temperature, B	<b>50</b>	°C	ISO 306

<b>Other properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Density	<b>905</b>	kg/m <sup>3</sup>	ISO 1183

**Characteristics****Features**

Copolymer