

| <b>Thermal properties</b>           | <b>Value</b> | <b>Unit</b> | <b>Test Standard</b> |
|-------------------------------------|--------------|-------------|----------------------|
| <b>Other Standards<sup>S1</sup></b> |              |             |                      |
| Max. Service Temp., Intermittent    | 260          | °C          | -                    |

S: These properties are reported by the producer according standards that are different to our defaults.

| <b>Other properties</b>             | <b>Value</b> | <b>Unit</b>       | <b>Test Standard</b> |
|-------------------------------------|--------------|-------------------|----------------------|
| Bulk Density                        | 470          | kg/m <sup>3</sup> | -                    |
| <b>Other Standards<sup>S1</sup></b> |              |                   |                      |
| Density                             | 2190         | kg/m <sup>3</sup> | ASTM D 4894          |

S: These properties are reported by the producer according standards that are different to our defaults.

**Characteristics**

**Processing**

Pipe/Tube Extrusion, Other Extrusion, Coating

**Delivery form**

Powder

**Special Characteristics**

U.V. stabilized or stable to weather

**Features**

Tribologic Grade

**Chemical Resistance**

General Chemical Resistance, Solvent Resistance

**Certifications**

Food contact, Food approval 10/2011, Food approval FDA 21 CFR

**Regional Availability**

North America, Europe, Asia Pacific, South and Central America