

## Kraton D1192 ET

SBS

Kraton Polymers

### Product Texts

Kraton D1192 E is a clear linear block copolymer based on styrene and butadiene with bound styrene of 30% mass.  
Kraton D1192 ET- supplied as porous pellets dusted with talc.

Processing/Physical Characteristics	Value	Unit	Test Standard
<b>ISO Data</b>			
Melt flow index, MFI	1	g/10min	ISO 1133
Temperature	200	°C	-
Load	5	kg	-

Mechanical properties	Value	Unit	Test Standard
<b>ISO Data</b>			
Tensile Strength	33	MPa	ISO 37
Strain at break	1000	%	ISO 37
<b>ASTM Data</b>			
Shore A Hardness	70	-	ASTM D 2240
<b>Other Standards<sup>[5]</sup></b>			
Stress at 300% elongation	14.4	MPa	ISO 37

S: These properties are reported by the producer according standards that are different to our defaults.

Other properties	Value	Unit	Test Standard
Bulk density	400	kg/m <sup>3</sup>	-
<b>Other Standards<sup>[5]</sup></b>			
Density	940	kg/m <sup>3</sup>	ISO 2781

S: These properties are reported by the producer according standards that are different to our defaults.

### Characteristics

#### Processing

Coating

#### Features

Copolymer

#### Delivery form

Pellets

#### Chemical Resistance

Oxidation Resistance

#### Special Characteristics

Transparent

#### Regional Availability

North America, Europe, Asia Pacific, Near East/Africa