

## Hytrel® 60LW

TPC-X

Celanese

### Product Texts

**Hytrel® 60LW is a Polyester Elastomer Concentrate Developed for Enhancing Abrasion and Wear Resistance**

### Processing/Physical Characteristics

	Value	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melt volume-flow rate, MVR	<b>6</b>	cm <sup>3</sup> /10min	ISO 1133
Temperature	<b>220</b>	°C	-
Load	<b>2.16</b>	kg	-
<sup>[C]</sup> Density of melt	<b>910</b>	kg/m <sup>3</sup>	-

[C]: CAMPUS

### Thermal properties

	Value	Unit	Test Standard
<b>ISO Data</b>			
<sup>[C]</sup> Melting temperature, 10°C/min	<b>210</b>	°C	ISO 11357-1/-3

[C]: CAMPUS

### Characteristics

#### Processing

Injection Molding, Film Extrusion, Profile Extrusion, Sheet Extrusion, Other Extrusion, Coating, Calendering, Transfer Molding, Casting, Thermoforming

#### Delivery form

Pellets

#### Additives

Lubricants, Release agent

#### Features

Tribologic Grade

#### Regional Availability

North America, Europe, Asia Pacific, South and Central America